



MONITOR SPECIFICATIONS

High Resolution, 3 Mega Pixel, Flat Screen, LCD

Technology	<i>TFT AMLCD Dual Domain IPS</i>
Bit Depth	<i>10 bit (1024 shades of gray displayed)</i>
Display Card	<i>High Resolution Video Card Included</i>
Native Resolution	<i>3 Mega Pixel (2048 x 1536)</i>
Pixel Pitch	<i>0.207 mm</i>
Active Screen Diagonal	<i>528 mm (20.8")</i>
Active Screen Width	<i>423.9 mm (16.7")</i>
Active Screen Height	<i>318 mm (12.5")</i>
Viewing Angle	<i>170° (10:1 contrast)</i>
Dark Room Contrast	<i>Typical 900:1</i>
Luminance	<i>500 cd/m² Calibrated 700 cd/m² Maximum</i>
Light Output Stabilization	<i>Backlight Output Stabilization (BLOS)</i>
Digital Video Input	<i>DVI connector</i>
Display Configuration	<i>Portrait or Landscape</i>
Security	<i>Kensington lock slot</i>
Operational Temperature (maximum)	<i>0°C to 40°C</i>
Within Specifications (recommended)	<i>15°C to 35°C</i>
Safety	<i>CE Listed UL 1950 CSA (or CUL) 950 IEC 950</i>
Emission	<i>EN55022 Limit A FCC class A EN 61000-3-2</i>